An Indo-Malaysian Joint Venture

World Class Welding & Cutting Equipments

ARC MMA 200E

Single phase, Light Duty, Professional Welding Machine, IGBT, suitable for ARC and TIG welding processes

DO THE WELDING, FEEL THE DIFFERENCE

MMA 200E Features

- Light and Compact
- Energy Efficient
- Stable ARC
- Deep Penetration
- Over Voltage and Over Current Protection
- Suitable to weld all kinds of Basic Electrodes
- Suitable for scratch TIG
- Digital Display

Welds : Steel, Stainless Steel, Brass, Copper

Industries : General Fabrication, Sheet Metal Works, Light Engineering, Light Fabrication, Domestic & Industrial Maintenance, Hobbyists & DIY enthusiasts, Fitment to Mobile Service Vehicles and many more...

Reliable, Light Weight ARC Machine

CENX WIM – MMA 200E is an economically priced, Single Phase latest Inverter Technology Professional Welding Machine which works on a Single PCB with an inbuilt Cooling Fan. This welding machine is very light in weight and versatile. Hence it is easy to carry and very reliable for at site jobs.

+91 9876543210 wimindia.com

Energy Efficient

- Energy Efficient, produces **Stable ARC**
- Performs **Deep Penetration** welds
- Has inbuilt **Over Voltage and Over Current Protection**
- Suitable to weld all kinds of Basic Electrodes.

User Friendly Panel

- **LED indicators** for Power On and Warning
- **Digital Display** to set desired output amps
- **Bigger heavy duty output panel sockets**
- **Rocker Switch** and supplied with suitable **input Electrical cable** fitted with a ready to use **Plug Top.**

60% Duty Cycle

- 60% Duty Cycle
- Suitable for **continuous operation** in light welding structures.
- **(DC output)** Suitable for **TIG Welding** also
- Maximum electrode diameter : MS 6013 – 3.15 mm (10G).

Standard Accessories

- Welding Electrode Holder with Cable
- Earth Clamp with Cable
- Suitable End Connectors

Optional Accessories

- Gas Cooled TIG Torch
- Earth Clamp with Cable
- Argon Regulator
- Gas Flow Meter & Gas hose (TIG weld)

Technical Specifications : MMA 200E

R&D being a continuous process, specifications are subject to change without prior notice

Technical Specifications	MMA 200E
Input Voltage (V)	1Ph - 230 +/-15%
Frequency (Hz)	50/60
No Load Voltage (V)	65
Output Current Range (A)	10 - 140
Rated Input Current (A)	30
Output Voltage (V)	28
Duty Cycle @ 40 Degree C (%)	60
Efficiency (%)	85
Digital Display	Yes
Power Factor	0.9
Insulation Class	H
Protection Class	IP21
Weight (Kgs.)	4.5
Dimensions (mm)	350 x 170 x 290
Usable Electrode - MS 6013 (mm)	3.15
Panel Socket Size	1025
Series	Economy
Handle	Black
Front Panel Print	Single Colour

+91 9876543210 wimindia.com

An Indo-Malaysian Joint Venture

DO THE WELDING,
FEEL THE DIFFERENCE

1 YEAR WARRANTY | Available Globally | 50+ YEARS OF EXCELLENCE

SALES | SERVICE | SKILLING

wimindia.com

CenX WIM India
venkat@centroid.in
+919876543210